



WARN Industrial Winch

Model

Part Number

Motor Type

Olympus 22W-8X8-A-CRC Air Clutch

83616

24 Volt Permanent Magnet



The Olympus is the world's most powerful and efficient electric winch. This lightweight and compact winch is equipped with an Axial Flux Permanent Magnet Motor that provides amazing power and extreme duty cycle that rivals hydraulic performance. Waterproof construction and superior corrosion resistance along with an overload interrupt switch, provide excellent durability, safety, and performance.

- *Remote Control Assembly, 32' included
- *Wire Rope Tension Kit included
- *Fairlead included
- *Winch comes with CARC coating
- *75' x 1/2" WARN Construct 6 Wire Rope Assembly included


Accessories

Description:	Part Number
Wire Rope Assy- 1/2" x 75 ft-Construct 6	87551
Fairlead-Hawse-Black	87855
Remote Control-Severe Duty-32 ft	85394

Engineering Data

Rated Pulling Force:	22000 lbf	9979 kgf
Drum Barrel Diameter:	5.0 in	127 mm
Drum Flange Diameter:	8.0 in	203 mm
Distance Between Flanges:	8.0 in	203 mm
Recommended Maximum Wire Rope Diameter:	1/2 in	12.7 mm
Recommended Minimum Wire Rope Breaking Strength:	33600 lbf	15241 kgf
Approximate Shipping Weight:	236.0 lb	107.0 kg
Duty Cycle (intermittent per SAE J706 section 6.2):	N/A	N/A
Mounting Bolt Torque:	80 ft*lb	108 N*m
Maximum Layers of Wire Rope:	3	
Gear Reduction:	216:1	
Brake Type:	Spring Applied Disc	
Contactor / Remote Type:	Industrial contactor with 32' (9.8m) heavy duty remote	

Drum Rotation



Viewed from Motor End


Standards Compliance

1. -CE Machinery Directive 2006/42/EC
2. -CE Electromagnetic Compatibility 2004/108/EC

Performance By Layer- 1/2" (12.7 mm) dia. rope


Drum Layer	Line Load *			No Load Line Speed		Drum Capacity	
	lbf	kgf	kN	ft/min	m/min	ft	m
1	22000	9979	97.9	8.4	2.6	21	6.4
2	18615	8444	82.8	9.3	2.8	45	13.7
3	16133	7318	71.8	10.7	3.3	75	22.9

* Never exceed the Rated Pulling Force. Installation of a Rated Capacity Limiter is recommended.



First Layer Performance

Line Load		Current Draw	Line Speed		Duty Cycle
lbf	kgf	Amps	ft/min	m/min	min/10min
0	0	7	8.4	2.6	continuous
5000	2268	60	7.3	2.2	continuous
10000	4536	107	6.9	2.1	10.0
15000	6804	157	6.5	2.0	5.8
20000	9072	208	6.1	1.8	3.8
22000	9979	227	5.7	1.7	3.3



WARN INDUSTRIES, INC
Industrial Products





Customer Service (North America): 1.800.543.9276
Customer Service (International): 1.503.722.3008
FAX: 1.503.722.3000 www.warn.com

12900 S.E. Capps Road,
Clackamas, OR USA 97015









WARN Industrial Winch

Model	Part Number	Motor Type
Olympus 22W-8X8-A-CRC Air Clutch	83616	24 Volt Permanent Magnet



Units are given in [inches] millimeters, unless otherwise specified

Recommended Mounting- Always Observe Correct Drum Rotation			Electrical System Specifications
Pull from bottom of winch	Pull from bottom of winch	Pull from top of winch	650 CCA Battery Minimum
			All electrical connections must be clean and tight
Feet down	Feet forward	Feet forward	
Pull from top of winch	Pull from top of winch	Pull from top of winch	Electrical System Wiring Schematic
			See Operators Manual P/N 85221
Feet down without angle brace	Feet down with angle brace	Angle Braces Only	Notes:

WARN INDUSTRIES, INC
Industrial Products

Customer Service (North America): 1.800.543.9276
Customer Service (International): 1.503.722.3008
FAX: 1.503.722.3000 www.warn.com

12900 S.E. Capps Road,
Clackamas, OR USA 97015